

File E129884 **UL LISTED**

**D RANGE**

W<sup>2</sup> MINIMUM

SEE NOTE 1

OPTIONAL RIB

L

H

S

W<sup>1</sup> MINIMUM

3/8 HEX

5/8 - 18 SET SCREW SEE NOTE 2

3/8 DEEP

13/16

5/16 RADIUS

5/8 DIAMETER TYPICAL

STYLE 2 HAS 3 HOLES

STYLE 1 HAS 2 HOLES

STYLE	L	H	W <sup>1</sup>	W <sup>2</sup>	T	B	S	C <sup>1</sup>	C <sup>2</sup>	D RANGE
1.	2 9/16	1 3/16	1 39/64	1 31/64	1/4	1"	33/64	25/64	27/32	3/8 - 11/16
* 2	3 1/8	1 9/16	2 29/64	2 29/64	7/16	1 3/8	57/64	25/64	27/32	3/8 - 11/16 1 or 2

\* 3 WIRE HOLES

**PARTS ARE :**

1. MARKED - IHI LOGO\* 2S250 250 MCM - 6 CU9AL (U)
2. ALUMINUM 6061-T6
3. TIN - PLATED

**NOTES :**

1. MOUNTING HOLE LOCATION AND SHAPE MAY VARY, AND MAY BE THREADED.
2. SCREWS ARE TIN-PLATED ALUMINUM 2011-T3.

\*PER DRAWING 12380

<b>INTERNATIONAL HYDRAULICS</b> INCORPORATED			
TITLE <b>2S250</b>			
DWG. BY JDB	DATE 7-13-99	DRAWING NO 14135	REV 2
CHK. BY NHS	SCALE		

THIS DRAWING AND DESIGN ARE THE PROPERTY OF INTERNATIONAL HYDRAULICS INC., CLEVELAND, OHIO, AND MAY NOT BE DUPLICATED, USED FOR BASIS OF DESIGN OR MANUFACTURE WITHOUT THE WRITTEN PERMISSION OF INTERNATIONAL HYDRAULICS INC., CLEVELAND, OHIO.